

# Prasi: Protocol for Remote Authentication and Shared Information

How to interface with the Prasi system using PHP  
by Aurélien Botman

for version 1.2, September 2006

This document gives information about how developers should interface with Prasi from PHP scripts.

Prasi is open-source free software and may be obtained from <http://prasi.sourceforge.net>.

## Contents

<b>1</b>	<b>Preliminary notes</b>	<b>2</b>
<b>2</b>	<b>Configuration</b>	<b>2</b>
<b>3</b>	<b>The interface</b>	<b>3</b>
3.1	Authentication . . . . .	3
3.2	Data manipulation . . . . .	4
3.3	List of users . . . . .	4
3.4	Direct linking . . . . .	5
3.4.1	Authentication tasks . . . . .	5
3.4.2	Administrative tasks . . . . .	5
<b>4</b>	<b>Simple example</b>	<b>5</b>
<b>5</b>	<b>Contact details</b>	<b>6</b>
<b>A</b>	<b>Note of major changes between 0.6.x and 1.0</b>	<b>6</b>

## 1 Preliminary notes

The target PHP script (the ‘service’) can only interface with Prasi in ‘remote’ mode; ‘local’ mode is not available via the PHP interface.

All the instructions in this API assume that you already have the PHP PEAR library fully installed and functioning on your system. If you do not, or would prefer to use a non-PEAR dependent version, you can delete the ‘prasi-client.php’ file and replace it (by renaming) by the file ‘prasi-client-nopear.php’. This replacement is almost the same and is not dependent on the PEAR library.

## 2 Configuration

Prior to interfacing with Prasi, the service needs to provide three configuration files: one inside the Prasi data-tree, and two with the prasi-client.

We shall take a service called ‘myservice’ as our example. An example configuration file (prasi-tree) would be as follows:

```
service:name:myphpservice
service:version:1.0
service:contact:myphpservice.admincontact@mydomain.com
service:url:http://www.myremotedomain.com/myservice/myphpservice.php
service:gateway:http://www.myremotedomain.com/myservice/prasi-client.cgi
service:domain:www.myremotedomain.com
service:code:MYSECRET
default:myphpservice_pathdata
default:myphpservice_otherdata
suggest:myphpservice_otherdata:brown_hair
```

It can be seen that there are 3 types of configuration commands. Those starting with ‘service’ describe basic details about the service, such as its name, version, contact point, URL, gateway, domain and secret code. All these entries are mandatory. The difference between gateway and URL are that gateway points to prasi-client.cgi on the remote server, always, whereas URL points to the remote service. The ‘code’ is a secret password known only to the administrator. It must be common in both configuration files. It should never be told to anyone. If it is suspected of being known, just change the code (in both configuration files), users will have to re-login but the communication will be secure again. See the Prasi project website for a page giving details on how this mechanism works.

The keywords starting with ‘default’ and ‘suggest’ are relevant to user profile data and are not necessary for basic usage of Prasi. Note that contrary to local services, remote services do not implement the ‘require’ keyword<sup>1</sup>.

The ‘default’ keyword is followed by the name of a variable. This named data is set by the Prasi administrator at the time of configuring a user for a service. In the example given, the data ‘myphpservice\_otherdata’ is set by the administrator when adding the new user to the service. The service can then read and also modify that data (see Section 3.2).

Any fields in the ‘suggest’ commands are default values for variables defined in the ‘default’ commands, with which to pre-fill the web page form. So, in the example given, the data ‘myphpservice\_otherdata’ will have the value ‘brown\_hair’ pre-filled in the part of the form which asks

---

<sup>1</sup>Yet.

the user/admin for that value. This can help admins and users quickly fill in the form using values regarded by the service as ‘reasonable’ (since it defined them).

This all means that the service can rely on the information in the ‘require’ and ‘default’ blocks as being completed when the user accesses it, and there is some provision in place for admin-prefilled values and user-decided values.

This configuration file should be placed inside the Prasi data-tree, under the directory ‘remote-services’, and named ‘myphpservice.cfg’.

The other configuration file examples (the prasi-client ones) would be:

```
#!/usr/bin/perl
package PRASI;
$pcook = "prasi_remoteauth";
$purl = "http://www.mydomain.com/prasi/";
$clientcode = "SECRET";
package main;
return 1;
```

where pcook is the remote cookie name, purl the URL of the prasi SERVER, and clientcode the secret password code mentionned earlier in this subsection. This file should be saved as ‘prasi-client-config.pl’ in the same directory as the remote service, on the remote server.

```
<?php
$pcook = 'prasi_remoteauth';
$purl = "http://www.mydomain.com/prasi/";
$clientcode = "SECRET";
?>
```

where the variable have exactly the same values as in ‘prasi-client-config.pl’. This file should be saved as ‘prasi-client-config.php’ in the same directory as the remote service, on the remote server.

‘prasi-client.php’ and ‘prasi-client.cgi’ should then be copied to this same directory. Finally, a language choice should be made and the appropriate language files copied as ‘prasi-client-lang.pl’ and ‘prasi-client-lang.php’.

Finally, the remote service needs to know about Prasi. In the remote service script, simply ‘require\_once’ the file ‘prasi-client.php’. For example,

```
require_once('./prasi-client.php');
```

Your remote service should, in theory, now be configured to be used with Prasi.

## 3 The interface

### 3.1 Authentication

The function to call to check if a user is logged in is ‘prasi\_login’. It must be called after printing the Content-Type and before doing any user-specific processing.

```
$user = prasi_login('myphpservice',0);
```

The first argument is the service name. The second argument is either 1 or zero. The function checks whether the browsing user is logged in yet or not. If the user is logged in, \$user will be a string containing the username of the person.

If the user is not logged in yet, if called with 0 as second argument then nothing happens and the function returns an empty string "". Otherwise if called with 1, the function will re-route the user's browser to a login screen. After logging in the user is redirected back to the script (so the script is re-loaded with the same parameters).

## 3.2 Data manipulation

To save information about the current user in that user's global Prasi profile, issue the following call:

```
prasi_save($username,$data_name,$data_content,$service_name);
```

where the user's username is held in \$username. \$data\_name should be the name to save the information as for later retrieval. \$service\_name is the name of the service writing the data. To prevent different services from overwriting each other's data, the one restriction on the data\_name is that it contain the name of the service within it. For example, a sensible scheme would be to prefix the name with the name of your service, for example 'myphpservice.number\_of\_visits'. \$data\_content is then obviously what to save. The string may contain newlines<sup>2</sup>.

It is strongly recommended to issue a call to prasi\_data (see below) beforehand, to check that you are not about to overwrite information which already exists. prasi\_save does absolutely no checking of previous data and overwrites information without asking. The overwritten data cannot be recovered and the only solution might be to reconfigure a user for the service adversely affected.

A call to prasi\_save with an empty string for the data content will delete the profile file of that name. Limited checking is performed at present - only trusted services should ever be installed anyway.

To retrieve information about the current user from that user's global Prasi profile, issue the following call:

```
$content = prasi_data($username,$data_name);
```

where the user's username is held in \$username. \$data\_name should be the name the information was stored as in a call to prasi\_save(). The data is returned in \$content. The variable will be an empty string if an error occurred (for example, if no data was stored under that name). The resulting data may contain errant newlines.

You are not limited to data stored by your service; you can read in any data stored by any service provided you know the name the data was saved as.

Note that some non-service specific data is already stored by Prasi by default and may be accessed by any service, for example 'email', 'fullname', 'language' and 'ip'. 'password' is also accessible although that is a hash so is of limited interest. In the future the session key and expiry may also be available via this method, allowing you to re-write the prasi manager itself for example (that is already implemented as a service! You could roll your own if you don't like the default one...).

## 3.3 List of users

To obtain a list of all users on the prasi system, you can use the following call:

---

<sup>2</sup>Currently only local services – remote services will only be able to read/write the first line of the sent data.

```
$list = prasi_userlist($service);
```

with `$service` being null. If a string is specified for `$service`, the call will return only those users who have access to the service of that name. (This call can be useful to find the list of prasi administrators, for example.) The returned list is newline-separated.

## 3.4 Direct linking

### 3.4.1 Authentication tasks

It is not necessary to redirect the user each time to the Prasi forms to log them in or out – the appropriate forms can easily be printed from the service.

To produce a login form, 4 fields are needed: username ('user'), password ('pw'), return url ('return') and the action 'login':

```
<form action="/prasi/login.cgi" method="post">
<input type="submit" value="login">
<input type="text" name="user">
<input type="password" name="pw">
<input type="hidden" name="return" value="/subpath/myphpserviceURL">
<input type="hidden" name="action" value="login">
</form>
```

To produce a logout form, 2 fields are needed: the return url ('return') and the action 'logout':

```
<form action="/prasi/login.cgi" method="post">
<input type="submit" value="logout">
<input type="hidden" name="return" value="/subpath/myphpserviceURL">
<input type="hidden" name="action" value="logout">
</form>
```

### 3.4.2 Administrative tasks

Services who read the `prasi.admin` status flag are able to call `manage.cgi` directly. One hidden option (added in version 1.2) is that appending `closewindow=1` to the query string will result in the extra window being closed immediately once the action is finished (ie. the user is automatically returned to the calling service).

## 4 Simple example

This example assumes that you have already placed 'myphpservice.cfg' under 'remote-services' in the prasi data-tree, and all the files 'prasi-client.cgi', 'prasi-client.php', 'prasi-client-config.pl', 'prasi-client-config.php', 'prasi-client-lang.pl' and 'prasi-client-lang.php' inside the same directory as the following file (to be saved as 'myphpservice.php').

```
<?php
require_once('./prasi-client.php');
$user = prasi_login('myphpservice',1);
```

```

if(!$user) {print "No user is logged in.";exit;}
print 'You are user ' . $user . '. (so, correctly logged in)<br>';
$email = prasi_data($user, 'email');
print 'Your email address is ' . $email . '. (so, data fetching works)<br>';
$count = prasi_data($user, 'remote-test-counter');
$count++;
$status = prasi_save($user, 'remote-test-counter', $count, 'remote-test');
print 'Counter is ' . $count . ' and status is ' . $status . '. (so, data saving works, try reloading!)<br>';
?>

```

## 5 Contact details

If you would like to contact us regarding this document for any reason, please do contact us via the facilities provided on our website (<http://www.sourceforge.net/projects/prasi>). Please do also contact us if you require further clarification concerning any issue of integrating Prasi into your PHP scripts.

## A Note of major changes between 0.6.x and 1.0

The user with username “demo” is now hard-coded in Prasi as the demonstration user. All Prasi applications should expect to be accessed in demo-mode by this user. They must however ensure themselves that no unnecessary privileges are given to this user.

A further change is that new users are automatically added to the “prasi” service. Previously this step required a separate manual action from the Prasi administrator; now this action is no longer necessary. However it is the responsibility of the Prasi administrator to manually remove access from this service if it is undesirable.